

72-VOLT AC ELECTRIC OR 13.5-HP GAS ENGINE WITH CLOSED LOOP EFI

COMFORTABLE ROOM FOR 6 DURABLE PLASTIC FLIP REAR SEAT FRAME WITH ENCLOSED STORAGE

# EXPRESS<sup>™</sup> L6





#### **ELECTRIC**

## ADD EVEN MORE TO YOUR LIFE.

Outdo yourself by exploring more than ever before with the all-new Express L6 series. With room for 6, rugged tires, and higher ground clearance, you'll elevate everyone's expectations for a smooth, stylish ride. Boost your drive time with the unbeatable power of our exclusive 72-volt powertrain or choose the industry's first closed-loop EFI powertrain. It's time to start crossing things off your bucket list with the all-new Express L6, here to awaken your sense of adventure.

#### **KEY FEATURES**

- Spacious legroom and front room operator area
- · Smooth and quiet Paramount M/T Tires with Radial SPDR Wheel
- · Convertible rear seat with durable composite frame and built in storage
- · Headlights, Taillights and Brake Lights
- · Functional dash with versatile cup and technology holders and three storage areas
- · Dashboard Storage Pockets
- · Premium Steering Wheel
- · Large Fender Flares
- · Dual USB Ports
- · Multi-Function Speed, State Of Charge and Hour Meter Gauge (Electric Only)
- DC/DC Converter (Electric Only)
- 72-Volt AC Powertrain (Electric Only)
- Fuel Gauge (Gas Only)
- · Low Oil Indicator (Gas Only)

DIMENSIONS	
OVERALL LENGTH	144 in (364 cm)
OVERALL WIDTH	49 in (125 cm)
OVERALL HEIGHT (W/O ROOF)	55.5 in (141 cm)
OVERALL HEIGHT (W/ ROOF)	83 in (211 cm)
WHEEL BASE	97 in (245 cm)
FRONT WHEEL TRACK	38.5 in ( 98 cm)
REAR WHEEL TRACK	38.5 in ( 98 cm)
GROUND CLEARANCE  © DIFFERENTIAL	7.0 in (18 cm)

#### POWER

POWER		
POWER SOURCE	72 Volt DC	4 Cycle 24.5 cu in (401 cc)
VALVE TRAIN	N/A	Single Cylinder OHV
MOTOR TYPE	AC Induction	N/A
FUEL SYSTEM	N/A	Closed-Loop Electronic Fuel Injection
HORSEPOWER (KW)	22.4 hp (16.7 kW) Peak	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
ELECTRICAL SYSTEM	72 Volt	Starter/Generator - Solid State Regulator
BATTERIES (QTY/TYPE)	Six, 12 Volt Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal Start	
AIR CLEANER	N/A	Replaceable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank
BATTERY CHARGER	72V, 120/230 VAC, UL & CSA	N/A
SPEED CONTROLLER	350 Amp AC	N/A
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	Forward-Reverse
REAR AXLE RATIO	17:1	11.47:1 (Forward); 14.35:1 (Reverse)

#### PERFORMANCE

SEATING CAPACITY	6-Passenger	
DRY WEIGHT	1066 lb. (484 kg)	1150 lb (522 kg) (without battery)
CURB WEIGHT	1558 lb. (707 kg)	1190 lb (540 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)	
SPEED (LEVEL GROUND)	Up to 19 mph $\pm$ 0.5 mph (Up to 30.6 kph $\pm$ 0.8 kph)	

#### STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single Point Engagement
TIRES	MT Paramount, 23x10-14, Radial, SPDR Alloy Wheel

### BODY & CHASSIS

FRAME	Welded steel with E-coat and DuraShield™ powder coat
BODY & FINISH	Injection Molded TPO
AVAILABLE BODY COLORS	Black, Bright White, Electric Blue, Flame Red, Inferno Red, Metallic Charcoal, Ocean Grey, Platinum, Slate
AVAILABLE SEAT COLORS	Black, Grey on Black, White on Beige
AVAILABLE PREMIUM	Black, Grey, Mushroom







©2020 Textron Specialized Vehicles Inc. 82455-G15 (Rev. 12/2020)











Platinum







www.ezgo.com

