

# E-Z-GO® FREEDOM® RXV® 2+2

## **GO WHEREVER THE DAY TAKES YOU.**

This is your day, and the E-Z-GO Freedom RXV 2+2 can help you get the most from it. With all the premium features and enhanced comfort from the Freedom RXV, the Freedom RXV 2+2 adds room for the whole gang. So grab the kids and go wherever the day takes you!

#### STANDARD FEATURES

- ▶ 18-in turf tires
- ► Advanced IntelliBrake<sup>™</sup> technology
- ► Headlights, taillights & brake lights
- ▶ Horn
- ► Integrated cup, ball & tee holders
- ► Energy transfer bumpers
- ► Fuel gauge (gas only)
- ► State of charge meter (electric only)
- ► DC/DC converter (electric only)
- ► 48-volt battery charger (electric only)
- ► Fixed rear seat
- ▶ Deep cup holders
- ► Comfortable, contoured seats





DIMENSIONS		
Overall Length	105.5 in (268 cm)	105.5 in (268 cm)
Overall Width	47.0 in (119 cm)	47.0 in (119 cm)
Overall Height (w/o roof)	47.0 in (119 cm) (top of steering wheel)	47.0 in (119 cm) (top of steering wheel)
Overall Height (w/ roof)	75.0 in (191 cm) (top of sun canopy)	75.0 in (191 cm) (top of sun canopy)
Wheel Base	66.0 in (168 cm)	66.0 in (168 cm)
Front Wheel Track	34.5 in (88 cm)	34.5 in (88 cm)
Rear Wheel Track Clearance @ Differential	38.5 in (98 cm)	38.5 in (98 cm) 3.0 in (8 cm)
POWER	4.0 in (10 cm)	3.0 III (8 CIII)
Power Source	48 Volt DC	4-cycle, 24.5 cu in (401 cc) Low Emissions
Valve Train	N/A	Single-Cylinder OHV with Hemispheric Combustion Chamber
Motor Type	48 Volt AC	N/A
Horsepower (kW)	N/A	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
Electrical System	48 Volt	Starter/Generator, Solid State Regulator
Batteries (qty/type)	Four, 12 Volt Deep Cycle	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal	Pedal
Air Cleaner	N/A	Remote Intake, Industrial-Rated Dry Filter
Lubrication	N/A	Pressurized Oil System
Oil Filter	N/A	Spin-On
Cooling System	N/A	Air Cooled
Fuel Capacity	N/A	5.85 gallon (22 L)
Battery Charger	48V DC, UL/CSA	N/A
Speed Controller	235 Amp AC Controller	N/A
Drivetrain	Motor Shaft Direct Drive	Automatic, Continuously Variable Transmission (CVT)
Transaxle	Limited Slip Differential	Differential with Helical Gears
Gear Selection	Forward-Neutral-Reverse Integrated Into Key Switch	Forward-Reverse
Rear Axle Ratio	16.99:1	11.42:1 (Forward); 15.78:1 (Reverse)
Key Switch	Unique Group, Unique Individual	Unique Group, Unique Individual
rogrammable Golf Modes	Coastal, Mild Hill, Steep Hill	N/A
PERFORMANCE		
Seating Capacity	4-Passenger	4-Passenger
Ory Weight (w/o batteries)	674 lb (306 kg)	785 lb (356 kg)
Curb Weight	1,002 lb (455 kg)	825 lb (374 kg)
Vehicle Load Capacity	800 lb (360 kg)	800 lb (360 kg)
Outside Clearance Circle	19.2 ft (5.8 m)	19 ft (5.8 m)
Speed (level ground)	8-15 mph (13-24 kph)	14 mph $\pm$ 0.5 mph (23 kph $\pm$ 0.8 kph)
EERING & SUSPENSION		
Steering	Double-Ended Rack and Pinion	Double-Ended Rack and Pinion
Suspension	Front: Independent A-Arm Coil-Over Shock Rear: Mono-Leaf Spring With Hydraulic Shocks	Front: Independent A-Arm Coil-Over Shock Rear: Mono-Leaf Spring With Hydraulic Shocks
Service Brake	Induction Motor	Rear Wheel Mechanical Self-Adjusting Drum
Parking Brake	Automatic Electro-Magnetic	Self-Compensating, Single Point Engagement
-	Turf Tires 18 x 8.50-8 (4-ply rated)	Turf Tires 18 x 8.50-8 (4-ply rated)
Tires	V 10 V 1000 V	1
BODY & CHASSIS		Wolded Cteel with Douglas Cost Protection
	Welded Steel with Powder-Coat Protection	Welded Steel with Powder-Coat Protection
BODY & CHASSIS	Welded Steel with Powder-Coat Protection  Injection Molded TPO	Injection Molded TPO
BODY & CHASSIS Frame		I -



FRONT



BACK

#### LAR OPTIONS & SSORIES

- down windshield
- canopy
- ther enclosure
- signals
- el covers (silver spoke & gold spoke)
- sage holder
- ing glove box view mirror
- meter
- ery watering system (electric only) If bag attachment vertible rear seat

- altitude jetting (gas only)
- y-duty battery option (electric only)
- outlet
- port



### [CUSTOMIZABLE DEALER NAME HERE]

[Customizable Dealer Address] [Dealer City], [Dealer State], [Dealer ZIP] [Dealer Web Address]

